

50 mm MOTORISED HORIZONTAL ALUMINIUM BLIND

UCTOMED	BATTERY-POWERED MOTO
:USTOMER:	EB4 – BTE50
	EB6 – BLE35
	MOTORS – WIRED CONTROL
	TT GO S 6/19 NICE
	SONESSE 40 PA 6/20 SOMFY
Order No.	JA 06 Soft 6/26 ELERO
order reo.	JA 06 Comfort 6/26 ELERO
Ordered on	TT GO S 10/14 NICE
ordered on	 SONESSE 40 PA 9/12 SOMFY
Nata of dollinous	JA 09 Soft 9/26 ELERO
Date of delivery	 JA 09 Comfort 9/26 ELERO

POWERED MOTORS	MOTORS – RADIO CONTROLLED (230V)
	B12 – BEQ35–10
	SONESSE 40 RTS 6/20 SOMFY
	RolTop/T S5/30-868 ELERO
IRED CONTROL (230V)	JA 06 Comfort 6/26-868 ELERO
E	SONESEE 40 RTS 9/12 SOMFY
5/20 SOMFY	JA 09 Comfort 9/26-868 ELERO
EDO	

MOTORS - RADIO	CONTROLLED	lo – homecontrol (230V)
SONESSE 40 io	6/20 SOMFY	
SONESSE 40 io	9/12 SOMFY	

MOTION MOTORS – RADIO CONTROLLED (230V)
MOTION CM07, 24 mm 12 VDC, 0,7 Nm
MOTION CM07, 24 mm 12 VDC, 0,7 Nm with CM38 battery
MOTION CM06, 35 mm 6 Nm (integrated battery)
MOTION CM06 EVE, 35 mm 6 Nm (integrated battery)

Types of fixing brackets

(column 6)

A - standard

B - top bracket





C - extended bracket







Overall widt			Colour	cable outlet / charging port			Bracket (3)				Ladder Colour		Type of bottom rail		Set for tilt windows (steel cord)		Colour of wood accessories for	d		/OOD/AL. system ⁽⁵⁾			Roo access	IILD SAFETY (7) m children have to (compliant with he standard)						
(mm) (mm) (z)		QTY (pcs)	QTY (pcs)	QTY (pcs)	QTY (pcs)	QTY (pcs)	QTY (pcs)	QTY (pcs)	of tape		L R	A	В	С	no drill bracket ⁽⁴⁾	cord	tape	of ladder	steel	extruded	bracket B	bracket C	WOOD/AL. (complete system)	straight no per	sides	colo of la wood		Milled bottom rail ⁽⁶⁾	YES	NO Length of operating
1	2	3	4		5			6	no dr		7	8		9	+	brack	11	stra	with	12	AL	Mil		ball chain/pull cords 13						

Please note:

- 1 Min. width of the blind: 800 mm
- 2 Standard height tolerance equals max. + 15 mm.
- 3 If no option in column 6 is selected, bracket A will be used.
- 4 No drill bracket available in white only.
- 5 Available colours of wooden accessories (WOOD/AL. system) as in 50 mm wood slats catalogue.
- 6 Milled bottom rail comes with tape ladder only.
- 7 Control length according to the criteria before the blind was adapted to the Child Safety standard is 600 mm. If control length is not specified, manufacturer's standardisation will apply. There is a choice of control lengths ranging from 100 mm to 3400 mm (gradation every 100 mm).

Brackets used with side Comments: guide mechanism

(column 10)

Type B

Comments:				