

50 mm MOTORISED HORIZONTAL BAMBOO BLIND

CUCTOMED	BAI
CUSTOMER:	EB4 – BT
	EB6 – BL
	МОТО
	TT GO S 6
	SONESSE
Order No.	JA 06 Soft
	 JA 06 Com
Ordered on	TT GO S 10
Ordered on	 SONESSE
Data of delivery	JA 09 Soft
Date of delivery	 IA 09 Com

BATTERY-POWERED MOTORS						
	EB4 – BTE50					
	EB6 – BLE35					

MOTORS – WIRED CONTROL (230V)
TT GO S 6/19 NICE
SONESSE 40 PA 6/20 SOMFY
JA 06 Soft 6/26 ELERO
JA 06 Comfort 6/26 ELERO
TT GO S 10/14 NICE
SONESSE 40 PA 9/12 SOMFY
JA 09 Soft 9/26 ELERO
JA 09 Comfort 9/26 ELERO

MOTORS – RADIO CONTROLLED (230V)								
	B12 – BEQ35–10							
	SONESSE 40 RTS 6/20 SOMFY							
	RolTop/T S5/30-868 ELERO							
	JA 06 Comfort 6/26-868 ELERO							
	SONESEE 40 RTS 9/12 SOMFY							
	JA 09 Comfort 9/26-868 ELERO							

ľ	MOTORS - RA	DIO	CONTROLLED	lo – homecontrol (230V)
	SONESSE 40) io	6/20 SOMFY	
	SONESSE 40) io	9/12 SOMFY	

MOTION MOTORS – RADIO CONTROLLED
MOTION CM07, 24 mm 12 VDC, 0,7 Nm
MOTION CM07, 24 mm 12 VDC, 0,7 Nm with CM38 battery
MOTION CM06, 35 mm 6 Nm (integrated battery)
MOTION CM06 EVE, 35 mm 6 Nm (integrated battery)

Types of fixing brackets

(column 6)

A - standard

B - top bracket





C - extended bracket

No drill bracket (4)





				Control side		de Bracket (3)			Ladder					dows	Vala	ance	rail (5)	CHILD SAFETY (6)			
Overa	all width	Overall height	OTV ()	C-1						it (4)				Colour	(stee	l cord)			tom rs		children have access to ant with the standard) ^(7,8)
	nm) ⁽¹⁾	(mm) ⁽²⁾	QTY (pcs)	Colour of slats	L	R	А	В	С	drill bracket (4)	cord ladder	tape	adder	of ladder	bracket B	bracket C	straight	with sides	Milled bottom	VEC	NO
										No dri	COL	25 mm	38 mm		brack	brack	st	wit	Ξ	YES	Length of operating ball chain/pull cords
	1	2	3	4		5		(6				7		:	8		9			12

Please note:

- 1 Min. width of the blind: 800 mm.
- 2 Standard height tolerance equals max. + 20 mm.
- 3 If no option in column 6 is selected, bracket A will be used.
- 4 No drill bracket available in white only.
- 5 Milled bottom rail comes with 25/38 mm tape ladder only.
- 6 The CHILD SAFETY standard applies to EB4, MOTION CM-07, MOTION CM-06, MOTION CM-06 EVIE electric motors.
- 7 Should you select no option in column 12, the manufacturer will assume that the product is intended for rooms young children have access to (length of operating chains/cords compliant with PN-EN 13120:2014+A1 standard).
- 8 Non-standard control length (to be entered in column 12) ranges from 100 mm to 5000 mm (gradation every 100 mm). If control length is not specified, manufacturer's standardisation will apply.

Brackets used with side Comments guide mechanism

(column 8)

Type B Type C



Comments:		