

## 50 mm MOTORISED HORIZONTAL WOOD BLIND

CUSTOMER:	
Order No.	
Ordered on	
Date of delivery	

EB4 – BTE50	
LD4 DILSO	
EB6 – BLE35	

MOTORS – WIRED CONTROL (230V)
TT GO S 6/19 NICE
SONESSE 40 PA 6/20 SOMFY
JA 06 Soft 6/26 ELERO
JA 06 Comfort 6/26 ELERO
TT GO S 10/14 NICE
SONESSE 40 PA 9/12 SOMFY
JA 09 Soft 9/26 ELERO
JA 09 Comfort 9/26 ELERO

MOTORS – RADIO CONTROLLED (230V)							
B12 – BEQ35–10							
SONESSE 40 RTS 6/20 SOMFY							
RolTop/T S5/30-868 ELERO							
JA 06 Comfort 6/26-868 ELERO							
SONESEE 40 RTS 9/12 SOMFY							
JA 09 Comfort 9/26-868 ELERO							

MOTORS -	<b>RADIO</b>	CONTROLLED	lo – homecontrol (230V)
SONESSE	40 io	6/20 SOMFY	
SONESSE	40 io	9/12 SOMFY	

MOTION MOTORS – RADIO CONTROLLED
MOTION CM07, 24 mm 12 VDC, 0,7 Nm
MOTION CM07, 24 mm 12 VDC, 0,7 Nm with CM38 battery
MOTION CM06, 35 mm 6 Nm (integrated battery)
MOTION CM06 EVE, 35 mm 6 Nm (integrated battery)

## Types of fixing brackets

(column 6)

A - standard

B - top bracket





C - extended bracket

No drill bracket (4)





				Control side		Bracket <sup>(3)</sup>				Ladder				win	Set for tilt windows		ance	rail <sup>(5)</sup>	CHILD SAFETY (6)	
Overall width	Overall height	QTY (pcs)	Colour of slats						et <sup>(4)</sup>	_	tane	adder	Colour of	(stee	l cord)			ttom ri		children have access to ant with the standard) (7,8)
(mm) <sup>(1)</sup>	(mm) <sup>(2)</sup>	ζτι (ρεσ)	colodi ol sides	L	R	А	В	С	drill bracket (4)	cord ladder	шрс	tape ladder of ladder		et B	et C	straight	with sides	Milled bottom		NO
									No dril	COVC	25 mm	38 mm		bracket B	bracket C	stı	wit	Μ	YES	Length of operating ball chain/pull cords
1	2	3	4		5	6			7		8		9				12			

## Please note:

- 1 Min. width of the blind: 800 mm
- 2 Standard height tolerance equals max. + 20 mm
- 3 If no option in column 6 is selected, bracket A will be used.
- 4 No drill bracket available in white only.
- 5 Milled bottom rail comes with 25/38 mm tape ladder only.
- 6 The CHILD SAFETY standard applies to EB4, MOTION CM-07, MOTION CM-06, MOTION CM-06 EVIE electric motors.
- 7 Should you select no option in column 12, the manufacturer will assume that the product is intended for rooms young children have access to (length of operating chains/cords compliant with PN-EN 13120:2014+A1 standard).
- 8 Non-standard control length (to be entered in column 12) ranges from 100 mm to 3400 mm (gradation every 100 mm). If control length is not specified, manufacturer's standardisation will apply.

Brackets used with side Comments: guide mechanism

(column 8)

Type B





١.	
C	
A	