

50 mm MOTORISED HORIZONTAL WOOD BLIND FSC®

CUSTOMER:
.....

Order No.

Ordered on

Date of delivery


BATTERY-POWERED MOTORS	
EB4 – BTE50	
EB6 – BLE35	

MOTORS – WIRED CONTROL (230V)	
TT GO S 6/19 NICE	
SONESSE 40 PA 6/20 SOMFY	
JA 06 Soft 6/26 ELERO	
JA 06 Comfort 6/26 ELERO	
TT GO S 10/14 NICE	
SONESSE 40 PA 9/12 SOMFY	
JA 09 Soft 9/26 ELERO	
JA 09 Comfort 9/26 ELERO	

MOTORS – RADIO CONTROLLED (230V)	
B12 – BEQ35–10	
SONESSE 40 RTS 6/20 SOMFY	
RoITop/T S5/30–868 ELERO	
JA 06 Comfort 6/26–868 ELERO	
SONESSE 40 RTS 9/12 SOMFY	
JA 09 Comfort 9/26–868 ELERO	

MOTORS – RADIO CONTROLLED io – homecontrol (230V)	
SONESSE 40 io 6/20 SOMFY	
SONESSE 40 io 9/12 SOMFY	


MOTION MOTORS – RADIO CONTROLLED	
MOTION CM07, 24 mm 12 VDC, 0,7 Nm	
MOTION CM07, 24 mm 12 VDC, 0,7 Nm with CM38 battery	
MOTION CM06, 35 mm 6 Nm (integrated battery)	
MOTION CM06 EVE , 35 mm 6 Nm (integrated battery)	



Overall width (mm) ⁽¹⁾	Overall height (mm) ⁽²⁾	QTY (pcs)	Colour of slats	Control side		Bracket ⁽³⁾				Ladder		Colour of ladder	Set for tilt windows (steel cord)		Valance		Milled bottom rail ⁽⁵⁾	CHILD SAFETY ⁽⁶⁾		
				L	R	A	B	C	No drill bracket ⁽⁴⁾	cord ladder	tape ladder		bracket B	bracket C	straight	with sides		Room children have access to (compliant with the standard) ^(7, 8)		
											25 mm							38 mm	YES	NO
1	2	3	4	5	6				7			8	9			12				

- Please note:**
- 1 Min. width of the blind: 800 mm
 - 2 Standard height tolerance equals max. + 20 mm
 - 3 If no option in column 6 is selected, bracket A will be used.
 - 4 No drill bracket available in white only.
 - 5 Milled bottom rail comes with 25/38 mm tape ladder only.
 - 6 The CHILD SAFETY standard applies to EB4, MOTION CM-07, MOTION CM-06, MOTION CM-06 EVIE electric motors.
 - 7 Should you select no option in column 12, the manufacturer will assume that the product is intended for rooms young children have access to (length of operating chains/cords compliant with PN-EN 13120:2014+A1 standard).
 - 8 Non-standard control length (to be entered in column 12) ranges from 100 mm to 3400 mm (gradation every 100 mm). If control length is not specified, manufacturer's standardisation will apply.

Brackets used with side
guide mechanism
(column 8)



Comments: