

MONOCOMMANDO (MONO CHAIN) 50 mm HORIZONTAL WOOD BLIND

CUSTOMER:	Control side (column 5)	Types of fixing brackets (column 6)						
Order No. Ordered on		A – standard B - top bracket C - extended bracket No drill bracket (4)						
Date of delivery	∥ L R ∥	The state of the s						

				Control side			Bracket ⁽³⁾			Ladder		lder	Steel cord for tilt windows		Valance		rail (5)	CHILD SAFETY																			
Overall width (mm)	Overall height (mm) ⁽¹⁾	QTY (pcs)	Colour of slats			C-1				No drill bracket	lder	tape	ladder	ur of ladder	Bra	cket	ļt.	des	Milled bottom r		n children have access to iant with the standard) ^(6,7)																
																				L	R	Colour of mechanism (2)	А	В	С	C drill br	cord ladder	10 mm	25 mm	Colour	В		straight	with sides	Milled	YES	NO Length of operating
										8		10111111	2311111								ball chain/pull cords																
1	2	3	4		. 5	5 6		7		8		9		10																							

- 1. Standard height tolerance equals max. + 20 mm
- 2. Colour of monocommando gear unit: white, ivory, grey, golden oak, black, metal ball chain is used as standard.
- 3. If no option in column 6 is selected, bracket A will be used.
- 4. No drill bracket available in white only.
- 5. Milled bottom rail available with 10/25 mm tape ladder only.
- 6. Should you select no option in column 10, the manufacturer will assume that the product is intended for rooms young children have access to (length of operating chains/cords compliant with PN-EN 13120:2014+A1 standard).
- 7. Non-standard control length (please enter the value in column 10) ranges from 100 mm to 5000 mm (gradation every 100 mm). If control length is not determined, the blind will be produced in accordance with manufacturer's standardisation.

Brackets used with side Comments: guide mechanism

(column 8)

Type B

Туре	C
	3
	A

77-
\checkmark