

PLEATED BLINDS – EVIE EV2x2, EV3+ SYSTEM ORDER FORM

CUSTOMER:	Pleat syst	em (column 4)	Operating handle (column 11)			
	 EV2x2	EV3+	Type A	Type B		
Order No. Ordered on				46		
Date of delivery			Number of operating	handles <i>(column 12</i>		
	Ļ	Ļ				

Total width (mm)	Total height (mm)	Quantity (pcs)	Pleat system		Fabric	Colour of accessories														Types of tension		Adaptors ⁽³⁾		Operating handle		Number of		
								hite		_	еу	ite		ر م	gne	oak	L H	ster	Type of	Window profile		De ⁽²⁾			operating handle		operating handles ⁽⁴⁾	
			EV2x2	EV2x2 EV3+	top bo	bottom	white	cream white	beige	brown	basalt grey	anthracite	black	anod	silver champagne anode	anode golden oak	walnut	winchester	bracket (1)	height (Z) for type D bracket	Type 1	Type 2	Set of angle adaptors 7º, 25º, 45º	- Spacer	Type A	Type B	1 рс	2 pcs
1	2	3	4	4		5						e	6						7	8	9		10		11		12	

D - non-invasive, on


the casement frame

Please note:


- ⁽¹⁾ Type A bracket adjusted to the system of the pleat. Type B coupled with respective bracket A.
- ⁽²⁾ Type 1 tension shoe (reinforced) is included as standard. If bracket D is used, tension shoe is not included.
- ⁽³⁾ If column 10 is not selected, no adaptors will be provided.
- ⁽⁴⁾ The standard rail is fitted with one operating handle.1. The standard width of fabric equals total width
- (rail + end caps).
- 2. "Pearl" and "blackout" finish on the outer (left) side of fabric.








Height of window profile (Z) for type D bracket (column 8)



Types of tension shoe (column 9)



legible signature of the Customer